

8/PPTS

10/522931

DT05 Rec'd PCT/PTO 24 JAN 2005

WO 2004/014680 PCT/EP2003/006304

CONNECTION OF THE EDGES OF FORMED SHEETS

Specification:

The present invention pertains to a connection of the edges of formed sheets, preferably of a door for motor vehicles according to the preamble of claim 1.

The door outer sheet and the door inner sheet of motor vehicles are usually connected with one another by spot welding, tacking and tacking adhesive, whereby a permanent connection is established, which can usually be detached only by destroying or damaging the door outer sheet. The tacked doors are inserted into the body at the stage of the bodyshell. This makes difficult the current concepts of subcontracting the processing of already painted doors equipped with accessories. The goal is therefore to connect the inner door built up and painted separately with the door outer skin after the painting of the body and the door outer skin and to subsequently connect it with the body.

The basic object of the present invention is therefore to propose a detachable connection of the edges of such sheets, in which the tacking technique can be done away with.

This object is accomplished according to patent claim 1. The subclaims 2 through 9 contain

meaningful embodiments for this.

Provisions are made according to the present invention for the areas of the edges of the sheets lying on top of each other to have strips, straps and/or flanges bent inwardly and/or at least in the same direction for the detachable connection of the sheets by means of screw connections and/or clamping strips.

The edges of the sheets may be preferably manufactured by edging and designed such that mounting straps arranged approximately at right angles to the plane of the sheet are present, distributed on the circumference preferably on the door outer skin, and the said mounting straps can be fitted together into the inner sheet at opposite mounting flanges of the inner sheet and/or of a connecting sheet and detachably connected by means of a screw connection. Instead of or also in addition to the screw connection, the straps and flanges of the edges of the sheets may also be surrounded by a U-shaped clamping strip, preferably one made of plastic, which can be attached from the outside. It proved to be favorable in case of the use of clamping strips to have not only straps and flanges distributed on the circumference at the sheet edges, but also bent strips, which extend fully or partially over the circumference of the sheet edges. It is now also possible to use longer clamping strips, which preferably extend over the entire circumference or at least over a large part of the circumference. If these clamping strips have a greater length, they must, of course, be made correspondingly elastic or articulated for adaptation to the contours of the sheet edges. To stabilize the plastic clamping strip, it proved to be favorable if the plastic clamping strip has an inner metal core, which additionally holds the plastic strip on the connection.

As an alternative or in addition to the screw connection, the clamping strip may also be "clipped" or fixed by means of a clipping device in a common opening in the edges of the sheets.

Besides the two sheet edges and optionally also the plastic clamping strip, the joint sealing can also be screwed by means of the screw connection. As a result, the door outer sheet is connected with both the door inner sheet or with a connecting sheet and the joint sealing. However, the joint sealing may also be integrated in the plastic clamping strip such that both are permanently connected with one another already at the time of the manufacture. In this case, the joint sealing does not need to be directly included in the screw connection any longer.

Finally, it also proved to be favorable to design the clamping strips such that they act as cover strips at the same time and even assume the outer sealing function itself. These cover strips can then be brought into contact with the door outer sheet in a suitable manner, e.g., elastically, and be in contact on the other side, e.g., with the glass or the rocker panel.

The connection according to the present invention has the following advantages:

- Elimination of the tacking unit,
- the new concept of the separate painting of the door outer skin and the inner door can be applied,
- a connecting sheet may be bonded, soldered or welded to the door inner sheet or permanently connected with same in another manner, i.e., no screw connection is necessary, because the connecting sheet and the door outer skin are detachably connected with one another,
- the outer skin, which is removable as an individual part, offers increased repair-

friendliness, and

-joint sealings can be integrated in cover profiles and clamping strips in a simple manner.

The present invention will be explained in greater detail below as an example on the basis of Figures 1 through 8 attached. In the drawings,

Figure 1 shows the view of a locally screwed outer skin 1 in the area of the C pillar of a passenger car;

Figure 2 shows an enlarged detail "x" from Figure 1;

Figure 3 shows the edge connection of a locally screwed outer skin 1 in the area of the C pillar;

Figure 4 shows an arrangement corresponding to that in Figure 3 with a clamping strip 8 and joint sealing 13 integrated in the clamping strip;

Figure 5 shows an arrangement corresponding to Figure 3 with a clamping strip 7 and joint sealing 12 integrated in the clamping strip for the area of a B column;

Figure 6 shows a connection from the area of the window channel with a clamping and cover strip 9 with integrated metal core 15 (without screw connection);

Figure 7 shows a connection with a clamping and cover strip 10 with integrated metal core 16 and an outer sealing 17 made integrally in one piece for the area of the rocker panel of a door, and

Figure 8 shows a connection of a clipped clamping and cover strip 11 with an outer sealing 18 made integrally in one piece, likewise in the area of a rocker panel of a door.

Figure 1 shows the arrangement of various mounting straps 3 on a door outer skin 1, which are connected with one another with the corresponding mounting flanges 4 of a connecting sheet 2 by a screw connection 5 shown in Figure 3. A sealing adhesive 6 is introduced in the area of the planar contact to seal the door outer skin 1 and the connecting sheet 2.

Compared to Figure 3, a U-shaped clamping strip 8 is additionally placed in Figure 4 on the bent edges of the sheets 1 and 2 and rigidly connected with the screw connection 5. The joint sealing 13 was rigidly connected with the plastic clamping strip 8 already at the time of the manufacture thereof or it may be connected with it later. The broken line 21 in Figure 4 indicates the adjoining contour of the C pillar, which is pressed by the joint sealing 13 with the door closed.

Figure 5 shows the adjoining B pillar, designated by reference number 20, with which the joint sealing 12 is in contact. In addition, the clamping strip 7 with the integrated joint sealing 12 is connected in Figure 5 with the edges of the sheets 1 and 2 by means of a screw connection. A sealing adhesive 6 is in turn present between the two sheets 1, 2 for additional sealing.

The screw connection 5 has been eliminated in Figures 6 through 8. The clamping strips 9 and 10

have, instead, an integrated metal core 15, 16 in Figures 6 and 7, and the edges of the sheets 1 and 2 are held together by means of the said metal core. In addition, the outer edge of the sheet 1 is bent in Figure 6 to the extent that it slightly surrounds the outer edge. At the same time, the bent outermost edge 22 of the sheet 1 may act as a retaining means for the clamping strip 9. The bent outer edge 23 of the sheet 2 may similarly act according to Figure 7 as a retaining means for the clamping strip 10. As is apparent from Figure 6, the clamping strip 9 additionally has elastic sealing lips, which are in contact with the pane 14.

Outer sealings 17 and 18, which come into contact with the door sill, not shown, are present in Figures 7 and 8.

According to Figure 8, the clamping strip 11 is held at the bent edges of the sheets 1 and 2 by means of the clipping device 19, so that retaining means similar to that for the edges 22 and 23 according to Figures 6 and 7 can be eliminated.

List of Reference Numbers:

- 1 Door outer sheet (door outer skin)
- 2 Connecting sheet
- 3 Mounting strap on 1
- 4 Mounting flange on 2
- 5 Screw connection
- 6 Sealing adhesive
- 7 Clamping strip
- 8 Clamping strip with integrated joint sealing 13
- 9 Clamping and cover strip with integrated metal core 15
- 10 Clamping and cover strip with integrated metal core 16 and outer sealing 17
- 11 Clamping and cover strip with outer sealing 18
- 12 Joint sealing
- 13 Joint sealing on 8
- 14 Glass
- 15 Metal core in 9
- 16 Metal core in 10
- 17 Outer sealing on 10
- 18 Outer sealing on 11
- 19 Clipping device for 11
- 20 B pillar

21 C pillar

22 Edge for 1

23 Edge for 2